

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/EP05/000795

International filing date: 27 January 2005 (27.01.2005)

Document type: Certified copy of priority document

Document details: Country/Office: EP  
Number: 04002422.6  
Filing date: 04 February 2004 (04.02.2004)

Date of receipt at the International Bureau: 15 March 2005 (15.03.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

**Patentanmeldung Nr.    Patent application No.    Demande de brevet n°**

04002422.6

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

**R C van Dijk**

2010-01-01



Anmeldung Nr:  
Application no.: 04002422.6  
Demande no:

Anmeldetag:  
Date of filing: 04.02.04  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

DSM IP Assets B.V.  
Het Overloon 1  
6411 TE Heerlen  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se referer à la description.)

Process for the preparation of methylheptenone

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

C07C45/00

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

3-11-60 10:00 AM

# *Fax Cover Sheet*

---

<b>To:</b>	<b>Europäisches Patentamt, München</b>	<b>Tel. +49 89 23 99-0 Fax +49 89 23 99 44 65</b>
------------	--	---

---

**Copies:**

---

<b>From:</b>	<b>Dr. L. Grossner</b>	<b>DSM IP Assets B.V. Het Overloon 1 NL- 6411 TE Heerlen The Netherlands Tel. +41-61-687 09 56 Fax +41-61-688 32 41</b>
--------------	------------------------	---

---

---

<b>Date:</b>	<b>February, 4, 2004 PQ</b>
--------------	-----------------------------

---

---

<b>No. of pages:</b>	<b>12 (incl. cover sheet)</b>
----------------------	-------------------------------

---

DSM IP Assets B.V., NL-6411 TE Heerlen, The Netherlands

Case 22239

Process for the preparation of methylheptenone

5 The present invention relates to a novel process for the preparation of 2-methyl-2-hepten-6-one, hereinafter referred to also as methylheptenone. It is known to prepare methylheptenone by reaction of 2-methyl-3-buten-2-ol with isopropenyl methyl ether in the presence of catalysts, e.g phosphoric acid, see DE 1 193 490 or organic phosphates or phosphbinates, see DE 196 49 564.

10

It has been found that hydrogen bis(oxalato)borates and, particularly, hydrogen tris(oxalato)phosphates are especially well suited to catalyze the reaction. Accordingly, the present invention is concerned with a process for the preparation of 2-methyl-2-hepten-6-one which comprises reacting 2-methyl-3-buten-2-ol with isopropenyl methyl ether in  
15 the presence of hydrogen tris(oxalato)phosphate or hydrogen bis(oxalato)borate.

The process of the present invention can be carried out at normal pressure or at elevated pressure. Preferably, the reaction is carried out at elevated pressure, e.g at a pressure of about  $10^5$  to about  $20 \times 10^5$  Pascal (Pa), preferred  $5 \times 10^5$  to about  $15 \times 10^5$  Pa. Further, the  
20 reaction according to the present invention is preferably carried out in the absence of a solven. The catalyst can be added in pure form or solved, preferred is the solved form in acetone or methanol. The reaction is suitably carried out at elevated temperature, e.g. at a temperature between about 373 K and about 450 K. The molar ratio of the reactants is suitably about 1 : 1 to 1 : 3, preferred is 1 : 2 to 1 : 2.5 although an excess of one of the  
25 reactants, e.g., an excess of the less expensive reactant, isopropenyl methyl ether, may be

PA/PQ 4.2.2004

used and, if desired, be recycled after isolation of the desired reaction product from the reaction mixture.

The catalysts, hydrogen tris(oxalato)phosphate or hydrogen bis(oxalato)borate, may be present in the reaction mixture in amount to provide a substrate/catalyst ratio of about 1000:1 to about 100:1, preferably about 900:1 to about 300:1, based on 2-methyl-3-buten-2-ol as the substrate. Hydrogen tris(oxalato)phosphate can be prepared as disclosed in EP 1 227 089. Hydrogen bis(oxalato)borate can be prepared by the procedure described in EP 784 042.

10

The invention is illustrated further by the Example which follows.

#### Example

15 The reaction was carried out using an equipment the main part was a stainless steel batch reactor (Medimex - High Pressure) with a nominal volume of 1.0 liter, an operative temperature up to 493 K and a maximum pressure of 20 bar. The reactor was equipped with a heating system ( electrical heating spirals located in the jacket), a cooling system ( glycol-water mixture flowing through the reactor jacket), a temperature control for the measurement of the inner reactor, jacket and cooling temperatures, and a stirrer. The reactor was coupled with a laboratory vacuum pump to remove the air from the reactor. The sampling was done via a stainless steel capillary and a thin spiraled stainless steel tube connected to the sampling flask. The catalysts were used as about 12 or 5.5 wt.-% solution in methanol or 6.5 wt.-% solution in acetone (hydrogen bis(oxalato)borate), or about 12, 25 10 or 8 wt.-% solution in methanol or 6 wt.-% solution in acetone (hydrogen tris(oxalato)phosphate).

195 g MBE (2.22 mol), catalyst (see Table 1) and 342 g IPM (4.6 mol = 2.1 eq.) were mixed and charged into the reactor. The reactor was shortly evacuated with a vacuum pump. The reaction mixture was heated up to 423 K while stirring and maintaining said temperature. Samples were taken in appropriate time intervals through the sample valve and capillary and were directly neutralized with sodium acetate. The samples were analyzed by gas chromatography (NORM%). After the reaction mixture was cooled to room temperature a sample of the remaining reaction mixture was taken (no gas phase) and analyzed by gas 35 chromatography (NORM%).

The results are shown in Tables 1, 2 and 3 below.



- 3 -

Table 1

Catalyst (mol-%) <sup>1</sup>	Catalyst solution	T (K)	Reaction time (h)	Conversion of MBE (%)	Yield MH (%)
HOB (0.15)	5.5 % methanol	423	21.7	25.0	23.9
HOB (0.10)	5.5% methanol	423	24	29.9	29.5
HOB (0.10)	6.5 % acetone	423	24	48.0	23.3
HOB (0.05)	6.5 % acetone	423	24	35.7	20.1
HOB (0.01)	6.5 % acetone	423	24	16.6	14.4
HOP (0.15)	10.0 % methanol	423	21.3	96.3	91.0
HOP (0.15)	11.7 % methanol	423	24	97.7	92.5
HOP (0.15)	11.7 % methanol	423	24	97.9	97.7 <sup>2</sup>
HOP (0.15)	11.7 % methanol	423	24	97.6	97.6 <sup>2</sup>
HOP (0.12)	10.0% methanol	423	21.5	96.7	80.6
HOP (0.09)	10.0 % methanol	423	17	81.5	80.8
HOP (0.23)	10.0 % methanol	398	25	87.1	80.2
HOP (0.17)	10.0 % methanol	398	22	77.5	77.3 <sup>2</sup>
HOP (0.15)	6.1 % acetone	423	24	94.9	56.4

- 4 -

Table 2

HOB (0.9)	11.6 % methanol	423	24	50.3	43.2
HOB (0.3)	11.6 % methanol	423	24	22.0	20.3 <sup>1</sup>
HOB (0.3)	11.6 % methanol	423	24	28.5	26.1 <sup>3</sup>
HOB (0.3)	11.6 % methanol	448	24	39.2	37.6
HOB (0.3)	5.5 % methanol	423	24	29.8	28.0

Table 3

HOP (0.14)	6.1 % acetone	423	24	98.6	98.6 <sup>1</sup>
HOP (0.30)	11.7 % methanol	423	8.5	94.0	90.1
HOP (0.30)	7.9 % methanol	398	24	88.3	83.4
HOP (0.30)	11.7 % methanol	423	24	99.0	81.1

s HOB : hydrogen bis(oxalato)borate; HOP : hydrogen tris(oxalato)phosphate;  
MH : methylheptenone; MBE : 2-methyl-3-buten-2-ol; IPM : isopropenyl methyl ether

<sup>1</sup> based on MBE

<sup>2</sup> ratio IPM/MBE = 3.3/1 (all other cases 2.1/1), <sup>3</sup> ratio IPM/MBE = 2.5/1, <sup>4</sup> ratio IPM/MBE = 3.0/1

- 5 -

What is claimed is:

1. Process for the preparation of 2-methyl-2-hepten-6-one which comprises reacting 2-methyl-3-buten-2-ol with isopropenyl methyl ether in the presence of hydrogen  
5 tris(oxalato)phosphate or hydrogen bis(oxalato)borate.
2. A process as in claim 1 wherein the reaction is carried out in the presence of hydrogen tris(oxalato)phosphate.
- 10 3. A process as in claims 1 or 2 wherein the reaction is carried out under elevated pressure.
4. A process as in claim 3 wherein the reaction is carried out at  $10^5$  to  $20 \times 10^5$  Pa.
- 15 5. A process as in claim 3 wherein the reaction is carried out at  $5 \times 10^5$  to about  $15 \times 10^5$  Pa.
6. A process as in any one of claims 1 to 5 wherein the catalyst is present in an amount to provide a substrate/catalyst ratio of about 1000:1 to about 100:1, based on 2-methyl-3-buten-2-ol as the substrate.
- 20 7. A process as in claims 1 or 4 wherein the catalyst is present in amount to provide a substrate/catalyst ratio of about 900:1 to about 300:1, based on 2-methyl-3-buten-2-ol as the substrate.
- 25 8. A process as in any one of claims 1 to 7 wherein the ratio of 2-methyl-3-buten-2-ol to isopropenyl methyl ether is 1:1 to 1:3.
9. A process as in any one of claims 1 to 7 wherein the ratio of 2-methyl-3-buten-2-ol to isopropenyl methyl ether is 1:1 to 1:2.5.

30

\*\*\*